

855 Purchase Order Acknowledgment

Functional Group ID=**PR**

Introduction:

This Draft Standard for Trial Use contains the format and establishes the data contents of the Purchase Order Acknowledgment Transaction Set (855) for use within the context of an Electronic Data Interchange (EDI) environment. The transaction set can be used to provide for customary and established business and industry practice relative to a seller's acknowledgment of a buyer's purchase order. This transaction set can also be used as notification of a vendor generated order. This usage advises a buyer that a vendor has or will ship merchandise as prearranged in their partnership.

Heading:

	<u>Pos. No.</u>	<u>Seg. ID</u>	<u>Name</u>	<u>Req. Des.</u>	<u>Max.Use</u>	<u>Loop Repeat</u>	<u>Notes and Comments</u>
M	010	ST	Transaction Set Header	M	1		
M	020	BAK	Beginning Segment for Purchase Order Acknowledgment	M	1		
			LOOP ID - N1			200	
	300	N1	Name	O	1		

Detail:

	<u>Pos. No.</u>	<u>Seg. ID</u>	<u>Name</u>	<u>Req. Des.</u>	<u>Max.Use</u>	<u>Loop Repeat</u>	<u>Notes and Comments</u>
			LOOP ID - PO1			100000	
	010	PO1	Baseline Item Data	O	1		n1
			LOOP ID - PID			1000	
	050	PID	Product/Item Description	O	1		
			LOOP ID - ACK			104	
	270	ACK	Line Item Acknowledgment	O	1		
			LOOP ID - SCH			200	
	310	SCH	Line Item Schedule	O	1		n2

Summary:

	<u>Pos. No.</u>	<u>Seg. ID</u>	<u>Name</u>	<u>Req. Des.</u>	<u>Max.Use</u>	<u>Loop Repeat</u>	<u>Notes and Comments</u>
			LOOP ID - CTT			1	
	010	CTT	Transaction Totals	O	1		n3
M	030	SE	Transaction Set Trailer	M	1		

Transaction Set Notes

1. PO102 is required.
2. The SCH segment is used to specify various quantities of items ordered that are to be scheduled. When this segment is used the unit of measurement code (SCH02) should always be identical to the unit of

measurement code in the associated PO1 segment (PO103) and the sum of values of quantity (SCH01) should always equal the quantity ordered (PO102) in the PO1 segment.

3. The number of line items (CTT01) is the accumulation of the number of PO1 segments. If used, hash total (CTT02) is the sum of the value of quantities ordered (PO102) for each PO1 segment.

Segment: **ST** Transaction Set Header
Position: 010
Loop:
Level: Heading
Usage: Mandatory
Max Use: 1
Purpose: To indicate the start of a transaction set and to assign a control number
Syntax Notes:
Semantic Notes: 1 The transaction set identifier (ST01) is used by the translation routines of the interchange partners to select the appropriate transaction set definition (e.g., 810 selects the Invoice Transaction Set).
Comments:

Data Element Summary

	<u>Ref. Des.</u>	<u>Data Element</u>	<u>Name</u>	<u>Attributes</u>
M	ST01	143	Transaction Set Identifier Code Code uniquely identifying a Transaction Set Refer to 004010 Data Element Dictionary for acceptable code values.	M ID 3/3
M	ST02	329	Transaction Set Control Number Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set	M AN 4/9

Segment: **BAK** Beginning Segment for Purchase Order Acknowledgment
Position: 020
Loop:
Level: Heading
Usage: Mandatory
Max Use: 1
Purpose: To indicate the beginning of the Purchase Order Acknowledgment Transaction Set and transmit identifying numbers and dates

Syntax Notes:

- Semantic Notes:**
- 1 BAK04 is the date assigned by the purchaser to purchase order.
 - 2 BAK08 is the seller's order number.
 - 3 BAK09 is the date assigned by the sender to the acknowledgment.

Comments:

Data Element Summary

	<u>Ref.</u>	<u>Data</u>	<u>Name</u>	<u>Attributes</u>
	<u>Des.</u>	<u>Element</u>		
M	BAK01	353	Transaction Set Purpose Code Code identifying purpose of transaction set Refer to 004010 Data Element Dictionary for acceptable code values.	M ID 2/2
M	BAK02	587	Acknowledgment Type Code specifying the type of acknowledgment Refer to 004010 Data Element Dictionary for acceptable code values.	M ID 2/2
M	BAK03	324	Purchase Order Number Identifying number for Purchase Order assigned by the orderer/purchaser	M AN 1/22
M	BAK04	373	Date Date expressed as CCYYMMDD	M DT 8/8
	BAK05	328	Release Number Number identifying a release against a Purchase Order previously placed by the parties involved in the transaction	O AN 1/30

Segment: **N1** Name
Position: 300
Loop: N1 Optional
Level: Heading
Usage: Optional
Max Use: 1
Purpose: To identify a party by type of organization, name, and code
Syntax Notes:

- 1 At least one of N102 or N103 is required.
- 2 If either N103 or N104 is present, then the other is required.

Semantic Notes:
Comments:

- 1 This segment, used alone, provides the most efficient method of providing organizational identification. To obtain this efficiency the "ID Code" (N104) must provide a key to the table maintained by the transaction processing party.
- 2 N105 and N106 further define the type of entity in N101.

Data Element Summary

Ref.	Data	Name	Attributes
<u>Des.</u>	<u>Element</u>	<u>Name</u>	<u>Attributes</u>
M	N101	98 Entity Identifier Code	M ID 2/3
		Code identifying an organizational entity, a physical location, property or an individual	
		Refer to 004010 Data Element Dictionary for acceptable code values.	
	N102	93 Name	X AN 1/60
		Free-form name	

- Segment:** **PO1** **Baseline Item Data**
- Position:** 010
- Loop:** PO1 Optional
- Level:** Detail
- Usage:** Optional
- Max Use:** 1
- Purpose:** To specify basic and most frequently used line item data
- Syntax Notes:**
- 1 If PO103 is present, then PO102 is required.
 - 2 If PO105 is present, then PO104 is required.
 - 3 If either PO106 or PO107 is present, then the other is required.
 - 4 If either PO108 or PO109 is present, then the other is required.
 - 5 If either PO110 or PO111 is present, then the other is required.
 - 6 If either PO112 or PO113 is present, then the other is required.
 - 7 If either PO114 or PO115 is present, then the other is required.
 - 8 If either PO116 or PO117 is present, then the other is required.
 - 9 If either PO118 or PO119 is present, then the other is required.
 - 10 If either PO120 or PO121 is present, then the other is required.
 - 11 If either PO122 or PO123 is present, then the other is required.
 - 12 If either PO124 or PO125 is present, then the other is required.
- Semantic Notes:**
- Comments:**
- 1 See the Data Element Dictionary for a complete list of IDs.
 - 2 PO101 is the line item identification.
 - 3 PO106 through PO125 provide for ten different product/service IDs per each item.
For example: Case, Color, Drawing No., U.P.C. No., ISBN No., Model No., or SKU.

Data Element Summary

<u>Ref.</u>	<u>Data</u>	<u>Name</u>	<u>Attributes</u>
<u>Des.</u>	<u>Element</u>		
PO101	350	Assigned Identification Alphanumeric characters assigned for differentiation within a transaction set	O AN 1/20
PO102	330	Quantity Ordered Quantity ordered	X R 1/15
PO103	355	Unit or Basis for Measurement Code Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken Refer to 004010 Data Element Dictionary for acceptable code values.	O ID 2/2
PO104	212	Unit Price Price per unit of product, service, commodity, etc.	X R 1/17
PO106	235	Product/Service ID Qualifier Code identifying the type/source of the descriptive number used in Product/Service ID (234) Refer to 004010 Data Element Dictionary for acceptable code values.	X ID 2/2
PO107	234	Product/Service ID Identifying number for a product or service	X AN 1/48
PO108	235	Product/Service ID Qualifier Code identifying the type/source of the descriptive number used in Product/Service ID (234) Refer to 004010 Data Element Dictionary for acceptable code values.	X ID 2/2
PO109	234	Product/Service ID Identifying number for a product or service	X AN 1/48

- Segment:** **PID** Product/Item Description
- Position:** 050
- Loop:** PID Optional
- Level:** Detail
- Usage:** Optional
- Max Use:** 1
- Purpose:** To describe a product or process in coded or free-form format
- Syntax Notes:**
- 1 If PID04 is present, then PID03 is required.
 - 2 At least one of PID04 or PID05 is required.
 - 3 If PID07 is present, then PID03 is required.
 - 4 If PID08 is present, then PID04 is required.
 - 5 If PID09 is present, then PID05 is required.
- Semantic Notes:**
- 1 Use PID03 to indicate the organization that publishes the code list being referred to.
 - 2 PID04 should be used for industry-specific product description codes.
 - 3 PID08 describes the physical characteristics of the product identified in PID04. A "Y" indicates that the specified attribute applies to this item; an "N" indicates it does not apply. Any other value is indeterminate.
 - 4 PID09 is used to identify the language being used in PID05.
- Comments:**
- 1 If PID01 equals "F", then PID05 is used. If PID01 equals "S", then PID04 is used. If PID01 equals "X", then both PID04 and PID05 are used.
 - 2 Use PID06 when necessary to refer to the product surface or layer being described in the segment.
 - 3 PID07 specifies the individual code list of the agency specified in PID03.

Data Element Summary

	<u>Ref.</u> <u>Des.</u>	<u>Data</u> <u>Element</u>	<u>Name</u>	<u>Attributes</u>
M	PID01	349	Item Description Type Code indicating the format of a description Refer to 004010 Data Element Dictionary for acceptable code values.	M ID 1/1
	PID05	352	Description A free-form description to clarify the related data elements and their content	X AN 1/80

Segment: **ACK** Line Item Acknowledgment

Position: 270

Loop: ACK Optional

Level: Detail

Usage: Optional

Max Use: 1

Purpose: To acknowledge the ordered quantities and specify the ready date for a specific line item

Syntax Notes:

- 1 If either ACK02 or ACK03 is present, then the other is required.
- 2 If ACK04 is present, then ACK05 is required.
- 3 If either ACK07 or ACK08 is present, then the other is required.
- 4 If either ACK09 or ACK10 is present, then the other is required.
- 5 If either ACK11 or ACK12 is present, then the other is required.
- 6 If either ACK13 or ACK14 is present, then the other is required.
- 7 If either ACK15 or ACK16 is present, then the other is required.
- 8 If either ACK17 or ACK18 is present, then the other is required.
- 9 If either ACK19 or ACK20 is present, then the other is required.
- 10 If either ACK21 or ACK22 is present, then the other is required.
- 11 If either ACK23 or ACK24 is present, then the other is required.
- 12 If either ACK25 or ACK26 is present, then the other is required.
- 13 If either ACK27 or ACK28 is present, then the other is required.
- 14 If ACK28 is present, then both ACK27 and ACK29 are required.

Semantic Notes:

- 1 ACK29 Industry Reason Code may be used to identify the item status. In addition, it may be used in conjunction with ACK01 to further clarify the status.

Comments:

Data Element Summary

	<u>Ref.</u>	<u>Data</u>	<u>Name</u>	<u>Attributes</u>
	<u>Des.</u>	<u>Element</u>		
M	ACK01	668	Line Item Status Code	M ID 2/2
			Code specifying the action taken by the seller on a line item requested by the buyer Refer to 004010 Data Element Dictionary for acceptable code values.	
	ACK02	380	Quantity	X R 1/15
			Numeric value of quantity	
	ACK03	355	Unit or Basis for Measurement Code	X ID 2/2
			Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken Refer to 004010 Data Element Dictionary for acceptable code values.	
	ACK04	374	Date/Time Qualifier	O ID 3/3
			Code specifying type of date or time, or both date and time Refer to 004010 Data Element Dictionary for acceptable code values.	
	ACK05	373	Date	X DT 8/8
			Date expressed as CCYYMMDD	
	ACK07	235	Product/Service ID Qualifier	X ID 2/2
			Code identifying the type/source of the descriptive number used in Product/Service ID (234) Refer to 004010 Data Element Dictionary for acceptable code values.	
	ACK08	234	Product/Service ID	X AN 1/48
			Identifying number for a product or service	
	ACK09	235	Product/Service ID Qualifier	X ID 2/2

Code identifying the type/source of the descriptive number used in
Product/Service ID (234)
Refer to 004010 Data Element Dictionary for acceptable code values.

ACK10	234	Product/Service ID	X AN 1/48
--------------	------------	---------------------------	------------------

Identifying number for a product or service

Segment: SCH Line Item Schedule
Position: 310
Loop: SCH Optional
Level: Detail
Usage: Optional
Max Use: 1
Purpose: To specify the data for scheduling a specific line-item
Syntax Notes:

- 1 If SCH03 is present, then SCH04 is required.
- 2 If SCH08 is present, then at least one of SCH09 or SCH10 is required.
- 3 If SCH09 is present, then SCH08 is required.
- 4 If SCH10 is present, then SCH08 is required.

Semantic Notes:

- 1 SCH12 is the schedule identification.

Comments:

- 1 SCH05 specifies the interpretation to be used for SCH06 and SCH07.

Data Element Summary

	<u>Ref.</u>	<u>Data</u>	<u>Attributes</u>
	<u>Des.</u>	<u>Element</u> <u>Name</u>	
M	SCH01	380 Quantity Numeric value of quantity	M R 1/15
M	SCH02	355 Unit or Basis for Measurement Code Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken Refer to 004010 Data Element Dictionary for acceptable code values.	M ID 2/2
M	SCH05	374 Date/Time Qualifier Code specifying type of date or time, or both date and time Refer to 004010 Data Element Dictionary for acceptable code values.	M ID 3/3
M	SCH06	373 Date Date expressed as CCYYMMDD	M DT 8/8
	SCH12	350 Assigned Identification Alphanumeric characters assigned for differentiation within a transaction set	O AN 1/20

Segment: **CTT** Transaction Totals

Position: 010

Loop: CTT Optional

Level: Summary

Usage: Optional

Max Use: 1

Purpose: To transmit a hash total for a specific element in the transaction set

- Syntax Notes:**
- 1 If either CTT03 or CTT04 is present, then the other is required.
 - 2 If either CTT05 or CTT06 is present, then the other is required.

Semantic Notes:

- Comments:**
- 1 This segment is intended to provide hash totals to validate transaction completeness and correctness.

Data Element Summary

	<u>Ref.</u> <u>Des.</u>	<u>Data</u> <u>Element</u>	<u>Name</u>	<u>Attributes</u>
M	CTT01	354	Number of Line Items Total number of line items in the transaction set	M N0 1/6
	CTT02	347	Hash Total Sum of values of the specified data element. All values in the data element will be summed without regard to decimal points (explicit or implicit) or signs. Truncation will occur on the left most digits if the sum is greater than the maximum size of the hash total of the data element. Example: -.0018 First occurrence of value being hashed. .18 Second occurrence of value being hashed. 1.8 Third occurrence of value being hashed. 18.01 Fourth occurrence of value being hashed. ----- 1855 Hash total prior to truncation. 855 Hash total after truncation to three-digit field.	O R 1/10

Segment: **SE** Transaction Set Trailer
Position: 030
Loop:
Level: Summary
Usage: Mandatory
Max Use: 1
Purpose: To indicate the end of the transaction set and provide the count of the transmitted segments (including the beginning (ST) and ending (SE) segments)

Syntax Notes:

Semantic Notes:

Comments: 1 SE is the last segment of each transaction set.

Data Element Summary

	<u>Ref. Des.</u>	<u>Data Element</u>	<u>Name</u>	<u>Attributes</u>
M	SE01	96	Number of Included Segments Total number of segments included in a transaction set including ST and SE segments	M N0 1/10
M	SE02	329	Transaction Set Control Number Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set	M AN 4/9