

Double Jacketed Buried Service Wire

Spec. 4284

GOPHER-RESISTANT RDUP (RUS) PE-86
ICEA S-86-634

Product Construction:**Conductors:**

- Solid annealed copper

Insulation:

- High density polyethylene

Pairing:

- Varying pair lays

Core Filling:

- 80°C filling and flooding compounds

Inner Jacket:

- Linear low density polyethylene

Shield:

- 0.005" corrugated copper-clad alloy steel tape

Rip Cord:

- Under the outer jacket

Outer Jacket:

- Black, linear low density polyethylene

Application(s):

- Intended for use in buried service application to the subscriber loops
- The shielding material provides resistance to gopher damage

Compliance:

- ICEA S-86-634
- RDUP 7 CFR 1755.860 (RUS PE-86) for 2 and 3 pair constructions, formerly PE-54 CCS

Packaging:

- Standard coils or on non-returnable plywood reels in lengths as shown above

**Nominal Cable Data**

CATALOG NUMBER	PAIRS AWG	O.D. INCHES	WEIGHT LBS/MFT	STANDARD LENGTH (FT)
2095061	2/22	0.32	57	2500
2095002	2/22	0.32	57	5000
2095151	3/22	0.34	65	1000
2095064	3/22	0.34	65	2500
2095016	3/22	0.34	65	5000
2095150	6/22	0.40	93	1000
2095065	6/22	0.40	93	2500
2095063	6/22	0.40	93	5000
2095067	3/24	0.31	55	2500
2095066	3/24	0.31	55	5000
2095068	6/24	0.36	74	2500
2095069	6/24	0.36	74	5000

Data subject to change without notice. Contact your Customer Service Representative for latest information.